



FOUNTAIN

IC Unit

Solvent Agitating Drum Washer

Product Data Sheet

Solvent Only



* Drum for display only;
drum sold separately.

Overview

Fountain products are designed and manufactured in the USA, with expertise in building commercial-grade equipment for industrial use spanning half a century. The designs incorporate advancements from modern technologies and materials, consider customer feedback, and aim to be leaders in the industry. The IC unit is a compact, well-valued, automatic cleaning machine designed to add value and free resources for other tasks. The air-powered basket rotates, agitating the parts and reducing cleaning time significantly. The IC Unit is intended for use with a 16-gallon drum (not included) with Stoddard solvents.

Function

Automatic agitating parts cleaning with an enclosed work volume is designed for optimal efficiency. Parts are immersed in a rotating basket to ensure thorough cleaning. This system is ideal for small components, allowing them to be inserted and cleaned over a designated period, providing a hands-free cleaning solution.

Application


Industrial Cleaning, Automotive Service/Repair, CNC Fabrication Rinse, Agricultural Fabricators, Agricultural Maintenance/Repair, Power Sports Shops, Government Municipalities, Aerospace, Post Processing, Military Service/Repair

Product Highlights




Lift out basket for easy load and unload of parts, with mesh bottom for automatic draining, supports 20 lbs.

Adjustable 60-minute timer and bell for cycle completion identification. (does not stop agitation)



Dial in the perfect pace with our speed control, effortlessly adjusting the agitation speed up or down based on your specific needs.

Adjustable drum ring clamp for ideal tension on 16-gallon drum.



**MADE IN THE
USA**



CALL: 1-800-325-3594
E-MAIL: CS@FTNLLC.COM
WEBSITE: WWW.FOUNTAININDUSTRIES.COM

Rev. A.3



FOUNTAIN

IC Unit

Solvent Agitating Drum Washer

Product Data Sheet

Features

- Air powered agitating motor
- Adjustable locking clamp for drum
- Lever-lock band for securing cover
- Lid with gasket seal
- 16-gallon drum capacity (drum sold separately)
- Rugged metal basket - 11½" diameter x 7½" depth
- 20 lbs. weight capacity
- Basket hookup for easy installation
- 60-min timer with bell indication of cycle complete
- Operates with 20 psi or more of air pressure
- Adjustable speed control with on/off switch
- Maximum fluid depth: 24"
- Minimum fluid depth: 10"

Standard Accessories


Parts Basket

Optional Accessories

16 Gallon Drum

Product Dimensions

Overall Dimensions: 16" L x 16" W x 31" H (installed on drum)
Shipping Dimensions: 19" L x 16½" W x 24" H
Shipping Weight: 50 Lbs.



Parts Basket



16-gal Drum

Electrical Configurations

Voltage	Phase	Freq	Current	Main Fuse	Heating Wattage
Not Applicable (air powered only)					
Air Configuration					
Min PSI	Max PSI	Min CFM	-	Operating PSI	Connection
20	100	1.8		60	¼" NPT

Solvent Only



CALL: 1-800-325-3594
E-MAIL: CS@FTNLLC.COM
WEBSITE: WWW.FOUNTAININDUSTRIES.COM