




Model CM60

INSTRUCTION AND OPERATION MANUAL

SOLVENT PARTS CLEANER

TABLE OF CONTENTS

I.	Introduction	4
II.	Safety Instructions and Information	5
A.	General Instructions	5
B.	Safety	6
C.	Fire	7
D.	First Aid (Medical instructions)	7
E.	Environmental	8
III.	Chemical Selection	9
IV.	Installation	10
A.	Shipping Damage	10
B.	Unpacking	10
C.	Location	11
i.	Product Dimensions	11
ii.	Clearance	11
iii.	Considerations	12
D.	Electrical Specifications	12
E.	Electrical Hook-Up	12
V.	Machine Controls and Adjustments	13
A.	Controls Overview Electric Version	13
B.	Controls Overview Air Version	13
C.	Controls Overview (INSIDE)	14
VI.	Start Up	15
VII.	Operation	17
A.	Preparation and Inspection	17
B.	Loading	17
C.	Unloading	18
D.	Shut Off	18
VIII.	Maintenance and Service	19
A.	Weekly	19
B.	Monthly	19
C.	Use Dependent	19
i.	Solution	19
ii.	Sludge	19
D.	Sample Maintenance Schedule	19
IX.	Troubleshooting	20
A.	No power to the unit	21
B.	The unit has power, the heat works, but the pump does not turn on	21
X.	Replacement Parts / Optional Parts	21
A.	Electric Version	22

B.	Air Version.....	23
XI.	Wiring Schematics	24
A.	Electrical 115V 1 PH	24
XII.	Warranty.....	25

I. Introduction

- Congratulations on the purchase of your Model CM60 Small Manual Tank Washer!
- This unit is a compact and versatile table top manual wash tank that brings floor-standing power to the work bench. This unit is available in electric or air configurations and is epoxy painted for solvent. A pump and flow-through wash brush provides hand-held cleaning power for all your washing needs.
- Read the entire manual before attempting to install or operate this machine.
- Carefully review the Safety Instructions and Information section and all CAUTION, WARNING, and DANGER information. This information will instruct you on how to use this equipment in a safe manner. Keep this manual along with the material Safety Data Sheets (SDS) for detergents in use. Always have this information in easy reach for the operator and all personnel working on or around the equipment.
- Familiarize yourself with the general Maintenance and Troubleshooting of the product. Follow these guidelines to help ensure a long and trouble-free experience. If there are any questions or concerns, please call your local dealer.
- The equipment described in this manual is subject to change. The manufacturer reserves the right to change equipment at any time as part of normal product improvement. Some improvements may have been made after this manual was printed. For the latest information on your equipment, contact the manufacturer.

II. Safety Instructions and Information

A. General Instructions

IMPORTANT SAFETY INSTRUCTIONS – SAVE THESE INSTRUCTIONS

- Read all instructions. Do not attempt to install or use this machine without reading this entire manual. Read and understand all labels, SDS, and this instruction manual before use. Use only as described in this manual. Use only manufacturer's recommended attachments.
- Read and understand the SDS of all chemicals you are introducing to the solution from washing parts.
- If you fail to read, understand, and follow all the procedures in this manual, you may cause or suffer personal injury.
- Do not operate equipment with a damaged cord or if the equipment has been dropped or damaged, until it has been examined by a qualified person.
- If an extension cord is necessary, a cord with a current rating equal to or more than that of the equipment should be used. Cords rated for less current than the equipment may overheat. Care should be taken to arrange the cord so that it will not be tripped over or pulled.
- Always unplug equipment from electrical outlet when not in use. Never use the cord to pull the plug from the outlet. Grasp plug and pull to disconnect.
- Always wear safety glasses or a full-face shield to protect against chemical splash. Everyday eyeglasses only have impact resistant lenses, they are not safety glasses.
- Keep hair, loose clothing, fingers, and all parts of body away from moving parts.
- Do **NOT** smoke, eat, or drink in the work area.
- To reduce the risk of fire, do not operate equipment in the vicinity of open containers of flammable liquids (gasoline). Do not spray aerosols into or around this machine. Install the equipment in an area away from heat, sparks, and open flame.
- Do not use compressed air to dry parts. Do not operate this product in a manner that will cause splashing or mist to form.
- In any emergency, turn off the unit.
- Keep cover closed whenever unit is not in use.
- Do not place parts or equipment on the electrical panel box. It is not designed to support heavy weight, and you run the risk of personal injury or damage to the product.
- Do **NOT** modify these machines.
- These parts washers may employ a safety feature called a fusible link that holds the cover open during use. Do **NOT** modify, alter, or obstruct the operation of the fusible link.
- Disconnect power to the unit before maintenance or servicing of the equipment.

B. Safety

- **CAUTION!** For Solvent Applications - Use **ONLY** mineral spirits based solvents. Do **NOT** use water-based cleaning solutions.
- For Solvent Applications - This equipment is designed for use only with mineral spirits based solvents (Stoddard solvent) with a flash point greater than 40°C (104°F). Do **NOT** add any other chemicals to the cleaning agent including, but not limited to, kerosene, fuel oil, gasoline, chlorinated solvents, brake cleaner, or detergents. The use of any other solvents could potentially cause a hazardous condition.
- For Solvent Applications - Do **NOT** leave solvent-soaked rags in parts cleaner or in uncovered containers.
- For Solvent Applications - Do **NOT** obstruct the cover. It is designed to close automatically in the event of a fire. The safety link and cover closing mechanism must be intact. Do **NOT** substitute with any other type of cover positioning device. Do **NOT** leave large objects in the parts cleaner or hang anything on the cover that could prevent the cover from closing in the event of a fire.
- For Solvent Applications - Do **NOT** contaminate cleaning solvents with gasoline, alcohol or flammable liquids.
- For Solvent Applications - When cleaning carburetors or other fuel supplying components: remove all gasoline into a proper disposal container before placing the component into the parts cleaner. Gasoline has a lower flash point than mineral spirits solvent. If gasoline is added, the flash point of the solvent may be lowered.
- For Solvent Applications - Do **NOT** spray aerosols into or around this machine. Install the equipment in an area away from heat, sparks, and open flame. Never put hot parts into the solvent.
- For Solvent Applications - Turn unit "OFF" and close lid when equipment is not in use. This will reduce solvent loss due to evaporation.
- **DANGER!** NEVER operate electrical equipment inside of parts cleaner.
- **DANGER!** This machine may utilize HIGH VOLTAGE electricity. ALWAYS disconnect power to the unit before removal of the electrical panel cover. Obtain the services of a qualified electrician for all electrical work.
- Make sure the parts cleaner is connected to a properly grounded power source. Check serial plate for power requirements.
- **WARNING!** Avoid contact with eyes or skin. Wear protective eyewear, gloves, and clothing. Operation should be conducted in a manner, which prevents splashing, or spillage. Any spills should be promptly and properly cleaned up. Soak up all spills with absorbent material. Remove and dispose of all soaked material in accordance with regulatory requirements.
- This machine may come with a door limit switch. **NEVER** modify or defeat the limit switch. An unsafe condition may occur if any unauthorized changes are made.
- Do **NOT** place heavy objects on edges or front of sink. Although this parts cleaner is designed to be stable, uneven weight distribution could cause a hazardous condition, over which the manufacturer has no control.

- This unit is NOT intended for outdoor operation. To reduce the risk of electric shock, do NOT use on wet surfaces or expose to rain.

C. Fire

- For Solvent Applications - This equipment is designed for use only with mineral spirits based solvents (stoddard solvent) with a flash point greater than 40°C (104°F). Do NOT add any other chemicals to the cleaning agent including, but not limited to, kerosene, fuel oil, gasoline, chlorinated solvents, brake cleaner, or detergents. The use of any other solvents could potentially cause a hazardous condition.

For Solvent Applications - Under certain conditions the solvent could burn. For your protection, a fusible link automatically closes the cover of the parts cleaner in the event that a fire occurs in the sink work area. The closed cover contains and smothers the fire inside the metal sink. Do NOT leave large objects in the parts cleaner or hang anything on the cover that could prevent it from closing in the event of a fire. Do NOT replace fusible link with any other device to hold cover up.

- Fire Extinguisher Type: ABC
- Use a fire extinguisher suitable for flammable liquids and electrical.
- Do NOT use water.
- Do NOT place flammable materials or aerosols on or near equipment.
- Keep the door closed when not in use.
- Be familiar with SDS and fire procedures of all chemicals used on and around the equipment and all chemicals introduced into the solution during the cleaning process.
- Always keep fire extinguisher and protective equipment accessible and near equipment.
- Contact your local fire department for further details.
- In an emergency, disconnect or unplug the electrical supply to the equipment.

D. First Aid (Medical instructions)

Please note that these First Aid precautions are for uncontaminated cleaning solutions only. Once the solution has been contaminated with oil, grease, antifreeze, etc., safety precautions should be adjusted according to the type of contaminant and the information presented within their SDS details.

- EYES:
 - Contact may cause slight to moderate irritation. For direct contact, flush eyes with water for 10-15 minutes or until the material have been removed.
 - Be sure to remove contact lenses if present and to lift the upper and lower lids during rinsing.
 - If irritation from vapors or mists develops, move the victim into fresh air. Get medical attention if irritation persists.
- SKIN:
 - Prolonged or repeated contact tends to remove skin oils, possibly leading to dermatitis.

- Wash skin with soap and water. Remove contaminated clothing, rinse shoes, and launder clothing before reuse.
- If irritation or pain develops or persists, seek medical attention.
- INHALATION (Breathing):
 - Prolonged exposure to concentrate-mist or vapor may cause mild irritation of nasal passages or throat. Remove to fresh air immediately.
 - Do not leave victim unattended. Get medical attention if irritation persists.
- INGESTION (Swallowing):
 - (Uncontaminated cleaning solution) Drink 4 to 8 ounces of water and seek medical attention.
 - DO NOT induce vomiting.

E. Environmental

Solutions become contaminated when used to clean grease, oils, grime, and other chemicals from parts. Used solution must be disposed of properly. Familiarize yourself with the SDS of the contaminants you are introducing from the cleaning process and follow disposal guidelines for these chemicals. Consult your local environmental management agency for additional guidance and other potentially hazardous materials compliance requirements.

- SPILLS:
 - Avoid spilling solution. Spilled solution can create slippery conditions, clean it up immediately. Close off area to traffic. Wear appropriate PPE to prevent eye and skin contact. Consult the SDS for instructions on clean up and disposal.
- LEAKS:
 - Contain leaks promptly. Notify local environmental authorities if necessary.
 - Do NOT remove devices designed to reduce evaporation except to process work or to perform maintenance.
- DISPOSAL:
 - Follow SDS guidelines and the guidance and compliance requirements of your local environmental management agency.

III. Chemical Selection

- For Solvent Applications - This equipment is designed for use only with mineral spirits based solvents (stoddard solvent) with a flash point greater than 40°C (104°F). Do NOT add any other chemicals to the cleaning agent including, but not limited to, kerosene, fuel oil, gasoline, chlorinated solvents, brake cleaner, or detergents. The use of any other solvents could potentially cause a hazardous condition.
- For Solvent Applications - Do NOT use machine with isopropyl alcohol.
- For Solvent Applications - Do NOT use machine with acetone.
- For Solvent Applications - Do NOT use machine with any solvent with flash point less than 40°C (104°F)
- If not using a manufacturer's supplied chemical, contact Fountain Industries with a supplied SDS of the chemical. Fountain Industries can provide feedback on the chemical to determine if it is safe to use with the machine and will not damage the machine or parts in the machine.

IV. Installation

Floor plan layout should include adequate access for maintenance, service, and repair. Clearance should allow full opening and closing of the door without obstruction. Install your parts cleaner on a flat, level surface in an area provided with adequate ventilation. Local exhaust ventilation should be used in areas of high vapor concentration. Provisions for determining and maintaining adequate ventilation are the responsibility of the operator.

WARNING! This unit is NOT intended for outdoor operation

A. Shipping Damage

Upon arrival, inspect the carton or crating and the equipment inside for damage. If any damage is found, notify your carrier immediately and save all materials for the carrier's inspector to examine. Failure to promptly report damage could result in denial of your claim.

IMPORTANT! Damage claim is the responsibility of the customer.

B. Unpacking


If no damage is found, proceed with breakdown of the carton or protective crating. The equipment is now ready to be lifted out and moved to its installation location.

CAUTION! We recommend only moving the unit when completely empty. If the unit does need to be relocated, drain the tank completely and move to the new location via safe means.

IMPORTANT! Inspect unit for loose nuts and bolts after shipping. Inspect wiring and wiring connections. Transport can be rough, and it can sometimes shake items loose.


C. Location

i. Product Dimensions



- All dimensions are in inches.
- Dry Weight: 37 lbs
- Wet Weight: 75 lbs (at 4.5 gallons)
- Loaded Weight: 125 lbs (with 50 lbs. load)

ii. Clearance



iii. Considerations

- Make sure the site is level and smooth
- The floor surface needs to be appropriate for supporting the weight and applied pressure of the unit.
- Plan space around the machine to allow access for maintenance, service, and repair. Refer to the clearance dimensions above as recommendations.
- Plan space in front of and above the machine to allow the door to fully open and close without interference.
- The machine may create steam or vapors. Make sure this steam or vapor will have no adverse effects on the surrounding area.
- The process of removing wet parts from the machine will inevitably result in some solution spilling on the floor. Consider traction mats around the machine and avoid placing the machine next to a walkway.

D. Electrical Specifications

System:

Voltage: 115 VAC

Freq: 60 hz

Phase: 1 PH

Amperage: 1 A

Largest Motor:

HP: 1/125 HP


FLA: 0.6 A

E. Electrical Hook-Up

- The voltage, phase, and current draw of the machine are listed above and on the serial number plate. The wiring diagram is listed below in this manual in the Wiring Schematic section.
- **IMPORTANT!** Always seek the service of a qualified electrician for all electrical work.
- **CAUTION!** Shipping and handling may have loosened one or more wire connections. An electrician should inspect all screw connections and terminal connections before connecting power. Loose connection can cause a hot zone at the loose connection and cause damage to wiring, components, and become a fire or electrical hazard.
- **IMPORTANT!** After power is supplied, an electrician should check the rotation of all motors. The electrician should also be present during “start-up” in case a problem arises.

V. Machine Controls and Adjustments

A. Controls Overview Electric Version




Pump On/Off Switch

- Illuminates when On and switch outputting power to the pump.
- IP65 Water protection rated switch

5-15R Outlet

- Provides always-on power for accessories like an overhead light kit
- Intended for light duty accessories. Do not use power tools or other high amperage devices. 1A maximum.

B. Controls Overview Air Version



Air supply hook-up, 1/4" NPT thread.


Incoming air regulator, set at factory to 20 PSI. Adjust to control flow rate through wash brush. Do NOT exceed 40 PSI or wash brush button will "stick" and not function.

C. Controls Overview (INSIDE)

- Lid Lever/Lock

Lid Lever/Lock

- Lever drops into slot to self hold lid in raised position.
- Lift up on lever to release lock and manually lower lid to closed position.
- Lever acts as a fusible link in case of fire, melting and letting the lid fall and smother flames.
- Do NOT modify, defeat, or remove this component.



VI. Start Up


IMPORTANT! Use only manufacturers recommended solutions in the machine. If an alternative solution is going to be used, reach out to the manufacturer with a SDS of the chemical so the manufacturer can review and approve the chemical for use in the machine. This is for both your and the machine's safety. Not doing so may cause risk of harm and risk of damage to components in the machine.

CAUTION! Only use the correct solution in the machine. This machine is powdercoat painted, it is intended to be used with a stoddard solvent like Naphtha mineral spirits.

The First Start Up procedure is a first run procedure performed on a new machine or machine that has not been used for an extended period. Follow the procedures below to prepare the unit for standard operation.

The First Start Up procedure begins after completion of the Installation process. All electrical connections have been checked, all nuts and bolts checked, and an electrician has set up and reviewed electrical including a check of motor rotation if applicable (for 3PH machines).

- 1) Before connecting power to the unit, make sure all switches are in the OFF position.
- 2) Fill the machine with solution to the maximum capacity defined below.
 - **MAX CAPACITY: 4.5 GAL**
 - **MIN LEVEL: 3.75 GAL**



Electric Version:

- 3) With control of the wash brush, turn the pump switch to the On position. Verify there is smooth, continuous flow from the pump through the wash brush.
- 4) If there are flow problems, inspect the wash brush for clogs. Inspect the pump inlet screen for debris blocking flow.
- 5) If the above does not fix flow, the pump inlet screen may need to be removed to inspect the pump impeller for debris. The impeller should spin freely without obstruction.
- 6) If all above actions don't produce flow and the switch is illuminated, there may be a fault with the pump, and the pump might require replacement.
- 7) If the switch light does not illuminate, there is likely an electrical supply issue or an internal wiring issue that requires further electrical troubleshooting.

Air Version:

- 1) The regulator is pre-set from the factory at 20 PSI. Adjustment is not necessary, but you can adjust the regulator up or down to control flow speed. Never exceed 40 PSI. If you find the wash brush button "stuck," lower the regulator PSI.
- 2) Connect the air supply to the regulator.
- 3) Once connected, the system is always "on." To test function, depress the brush on/off push button. With the button down, the diaphragm pump will run, and liquid should flow.
- 4) The regulator can be adjusted to control flow rate, but the brush push button will not function above 40 PSI.
- 5) If you experience flow issues, inspect liquid level and verify the inlet screen is fully submerged. Also inspect the inlet screen for debris and clean if necessary.
- 6) If you ever hear a constant air leak noise from the regulator or the diaphragm pump, that component likely needs replacement.


VII. Operation

IMPORTANT! Any person operating this machine shall first read and understand this instruction manual fully. Pay careful consideration to all of the prior sections in this manual. An operator should have good understanding of the machine. Be familiar with all the chemicals used and take the necessary safety precautions when working with and around the machine.

A. Preparation and Inspection

- 1) Before starting the machine in the morning, walk around and inspect for damage or leaks.
- 2) Open the door and check liquid level and top off with solution and at the correct mix ratio if applicable.
- 3) Inspect the washing components for damage. Inspect door function.
- 4) Verify there has been no modification or alteration to the machine which could introduce risk of harm
- 5) Verify there is no Lockout/Tagout or other notifications indicating the machine is damaged and dangerous to use.
- 6) Turn ON each function of the machine and verify operation.
- 7) Test any safety interlock on the machine to verify function.

B. Loading



DANGER! The maximum loading capacity of this machine is 50 lbs. This rating is a distributed load rating. This weight must be distributed evenly to achieve the 50 lbs. capacity rating safely.

IMPORTANT! The working height of this machine is approximately 5.8". Parts taller than 5.8" can fit, but the lid will not be able to be closed until taller parts are removed.

- 1) Verify no obstructions are in front of door before opening.
- 2) Carefully place parts into the parts washer.
 - **MAXIMUM DISTRIBUTED LOAD: 50 LBS**
 - When loading small and numerous parts, always distribute the weight evenly across the work area.
 - Very small parts may need to be contained within a parts basket or mesh container to prevent them from falling out of the work area.
 - When loading large and heavy part, always center the part and ideally over any supporting beam under the work area. If more than one large and heavy part is loaded, evenly distribute them across the work area.
 - If a very large and heavy part must be lowered, make sure the first contact point of the part is located over a main support structure. Then continue to lower the part fully and make sure the part is centered after completely lowered.
- 3) Verify the part fully clears any functional elements of the machine as to not cause risk of damage to the part or machine during the wash process.

C. Unloading

- 1) Verify there are no obstructions in front of door before opening.
- 2) Allow the parts to drip dry if possible. Do NOT use compressed air to dry parts.
- 3) Carefully remove parts. Pay careful attention to loading balance as you remove parts.
 - **CAUTION!** Parts may be slippery and difficult to hold when wet. Always wear appropriate PPE for the chemicals, temperature, and to protect eyes from splash or spray. When removing parts, drip from parts may wet the floor and may create hazardous walking conditions.
- 4) Close the door when finished to minimize evaporation losses from the machine.

D. Shut Off

- 1) Turn the pump switch to the OFF position. If equipped with a wash timer, the 0 position will automatically be the OFF position.
- 2) If the machine is equipped with a heater, It is recommended the heat switch remains in the ON position during the entire work period to maintain operating temperature. Heating may be left ON for as long as is beneficial for the work environment including overnight if the washer is required immediately the next workday. Some machines may be equipped with a 7-day programmable timer for automatic start and stop of the heating function based on operation needs.
- 3) For Solvent Applications - When not using the unit for extended periods of time, the pump switch or timer should be set to the OFF position. The unit will use nearly no power with functions in the OFF state, although electrical components remain energized. You may also shut off the main breaker power to the unit during inactive times. There is no harm in disconnecting the machine from power for an extended period.

VIII. Maintenance and Service

Following a proper maintenance schedule is crucial for machine performance and life. Neglect can cause poor operation or damage to components. Below is a recommended maintenance schedule. The needs of your machine and liquid solution will be unique to your operating environment. Track and adapt this recommendation to suit your specific needs. Proper and consistent maintenance is key in maintaining a healthy, high performing machine.

A. Weekly

- Check debris trays and filter screens on the machine for debris build up. These primary filtering devices can be easily removed, cleaned, and reinstalled. The machine may have several styles of filtering devices between the work area and solution area, between the solution and pump, and at the pump inlet. Familiarize yourself with the equipped filtering devices, inspect, and clean weekly.

B. Monthly

- Check all external hoses and plumbing for leaks or weaknesses and replace if necessary. Check the hoses during the wash cycle to see if bubbles form in the hose lining.

C. Use Dependent

i. Solution

Solution and machine maintenance are crucial to the performance of this machine. We recommend that the solution is monitored daily, and records are kept. This will provide a “baseline” of “clean” readings and will help determine when it may be time clean out the tank. This preventative maintenance will save your company time, effort, and money. Below is a sample maintenance report that is used to great extent to maintain the solutions.

ii. Sludge

IMPORTANT! Removing oil and sludge regularly can greatly promote the life of the cleaning solution and the effectiveness of the machine. Sludge sits on the bottom and cannot be seen. Clean out the tank within the first week of operation to get an idea of how fast sludge will form for your specific parts cleaning operation. Depending on the application, some businesses have to clean-out sludge at least weekly, while others can wait months.

- 1) Disconnect power to the machine.
- 2) Drain the solution to a holding tank or drum.
- 3) Scrape out any sludge from the bottom of the tank. Be careful not to damage any internal components like pump, float switch, or heating elements while cleaning the bottom of the tank. Waste sludge should be contained and handled according to the laws and regulations of the region.

D. Sample Maintenance Schedule

Model: _____ Current Solvent: _____

Month: _____

Date Loaded: ____/____/____

DATE	____/____/____	____/____/____	____/____/____	____/____/____
Tested By				

- The chart can be modified to include any relevant data that is necessary to run the machine. (Some items on this chart may not apply to all machines.) The chart should also include a section labeled “Comments”. Any maintenance performed on the machine, or the solution (e.g., changing the solution, adding detergent) can be recorded in this section, including the name of the involved personnel and the date.
- **IMPORTANT!** All service personnel shall read and familiarize themselves with this instruction manual. The service technician should follow all safety procedures and be familiar with machine operation, maintenance, and troubleshooting. A service personnel shall read and familiarize themselves with SDS of any chemicals and contaminants in the machine.
- Record and maintain contact information of your local dealer and service representative.
- Electrical troubleshooting and repair should be performed by a certified electrician. Contact your dealer for a local representative. If no recommended personnel are available, any industrial electrician local to your area can service this product. Replacement parts list and wiring schematics are listed later in this manual.

IX. Troubleshooting

IMPORTANT! All advanced troubleshooting should be performed by a certified electrician.

A. No power to the unit


- 1) Verify the unit is wired correctly.
- 2) Check the main circuit breakers in the supply circuit. If a breaker is tripped, reset and try operating the unit. If the breaker trips again, contact an electrician to troubleshoot the cause.
- 3) If equipped, check the main fuses on the unit. If any fuses are blown, replace and restart the unit. Monitor for additional failure. If fuses continue to blow, contact an electrician to troubleshoot the cause.

B. The unit has power, the heat works, but the pump does not turn on

- 1) If equipped, inspect the door safety interlock switch. Verify that it is being fully depressed when the door is closed. If not, adjust the door safety interlock switch following the procedure in the ADJUSTMENTS section of MACHINE CONTROLS AND ADJUSTMENTS.
- 2) If equipped, inspect the pump timer and verify it has been adjusted past the 10-minute mark. Does the timer count down?
- 3) If equipped and above checks have not resolved the issue, have an electrician inspect the pump timer and door safety switch for proper operation and determine if either component requires replacement. A DMM on the Ohm setting can easily verify if these components are functional.
- 4) **DANGER! Electrical - Disconnect the machine from all power sources.**
Check wiring connections and verify no loose connections to the motors
- 5) **DANGER! Electrical**
If equipped with a contactor, there should be an audible “click” and visual movement of the plastic piece at the center of the contactor indicator when the coil closes the contacts. Note, some contactors don’t have visual indication of the contact motions, and this style can not be visually observed or manually tested.
- 6) If equipped, if the contactor does not seem to operate, have an electrician verify the contactor coil is receiving the correct voltage. If the correct voltage is supplied to the coil inputs and the contactor does not close, then contactor is faulty and needs replacing.
- 7) Check for any obstruction that may prevent motor rotation.
- 8) Verify there is no blockage in the pump impeller.
- 9) Have an electrician check output voltage from the contactor supplying the motor. Verify the motor is wired correctly and is receiving electricity. If electricity is being supplied to the motor and it still does not function, the motor is likely damaged and requires replacing.


X. Replacement Parts / Optional Parts

A. Electric Version



ITEM NO.	PART NUMBER	DESCRIPTION
1	600001	LATCH,FUSEIBLE,HDPE
2	400001	BRUSH,FLO-THRU,SOLV/AQ
3	500000	PUMP,ELECTRIC,170GPH LG
4	400004	HOSE,3/8 ID,30R7
5	200002	SWITCH,ROCKER,STDP 250V 16A
6	200001	CORD,POWER,18/3 SJTOW 7.5 FT
7	200006	RECEPTACLE,SINGLE,125V 10A,BLACK


B. Air Version



ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
1	600001	LATCH,FUSEIBLE,HDPE	1
2	400006	REGULATOR,AIR,0-60 PSI 1/4 NPT	1
3	400008	NUT,AIR REGULATOR,1-3/16 - 12 UN,NYLON	1
4	500001	PUMP,AIR,FLO JET (VITON)	1
5	400004	HOSE,3/8 ID,30R7	0.207
6	400009	STRAINER,1/4-5/16 BARB,NYLON	1
7	400002	CLAMP,WORMDRIVE,1/4- 5/8 RANGE,SS	4
8	400002	CLAMP,WORMDRIVE,1/4- 5/8 RANGE,SS	1
9	100013	PLUG,PANEL,REC 0.9X1.15,PE,BLACK	1
10	400007	BRUSH,FLO-THRU,ANGLED W/BUTTON	1
11	400004	HOSE,3/8 ID,30R7	3.5

XI. Wiring Schematics

A. Electrical 115V 1 PH



XII. Warranty

LIMITED WARRANTY AND LIMITATION OF REMEDIES AND DISCLAIMER.

(1) Fountain Industries, LLC "Fountain" warrants the Equipment to be free from defects in material and manufacture and to conform to specifications for the Equipment at the time of shipment. This warranty is applicable only if the Equipment is installed, operated and maintained in accordance with factory recommendations and procedures, including, but not limited to, the use of Fountain's approved solutions or accessories. If any Equipment fails to conform to the specifications or samples or any defect in material or manufacture appears within twelve (12) months from the date of initial purchase by end user Fountain's entire liability, and Customer's or end user's exclusive remedy, shall be, to either repair or replace such defective Equipment, at Fountain's option, within a reasonable time after written notification thereof and return of the defective Equipment to Fountain.

(2) THIS WARRANTY IS MADE IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTY OF MERCHANTABILITY, THE IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE, ANY IMPLIED WARRANTY ARISING OUT OF COURSE OF DEALING OR OF PERFORMANCE, CUSTOM OR USAGE OF TRADE EXCEPT OF TITLE AND AGAINST PATENT INFRINGEMENT.

(3) LIMITATION OF LIABILITIES; TIME LIMIT FOR FILING ACTION. NEITHER PARTY SHALL UNDER ANY CIRCUMSTANCES BE LIABLE TO EACH OTHER FOR DAMAGES OF ANY KIND, INCLUDING, WITHOUT LIMITATION, DIRECT, INDIRECT, INCIDENTAL, SPECIAL OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, LOSS OF PROFITS, REVENUE OR BUSINESS) RESULTING FROM OR IN ANY WAY RELATED TO THE EQUIPMENT, ANY OF CUSTOMER'S PURCHASE ORDERS, THESE TERMS AND CONDITIONS OR THE TERMINATION OR NONRENEWAL THEREOF.

FOUNTAIN'S LIABILITY ON ANY CLAIM OF ANY KIND (INCLUDING NEGLIGENCE) FOR ANY LOSS OR DAMAGE ARISING OUT OF OR RESULTING FROM THIS AGREEMENT, OR FROM THE PERFORMANCE OR BREACH THEREOF, OR FROM THE EQUIPMENT FURNISHED HEREUNDER SHALL IN NO CASE EXCEED THE PRICE OF THE SPECIFIC EQUIPMENT WHICH GIVES RISE TO THE CLAIM. ALL SUCH LIABILITY SHALL TERMINATE UPON THE EXPIRATION OF THE WARRANTY PERIOD AS STATED HEREIN.

These limitations apply regardless of whether such damages are sought based on breach of contract, negligence, strict liability in tort or any other legal theory.

(4) Any action for breach of warranty or any other obligation under these Terms and Conditions must be commenced within one (1) year from the purported date of breach.

(5) Each limitation on liability or remedy set forth in these Terms and Conditions is independent of any other limitation or if they are otherwise held to be unenforceable, that shall not affect the validity of any other such limitation or remedy.

Fountain assumes no liability for any claims for injury or damages to persons or property arising from any chemical manufactured by Customers or by any third party vendors for use in any Fountain's equipment.

Terms or conditions contained in any Customer purchase order or similar document that in any manner purport to alter, modify, change, or suspend these terms shall be deemed excluded from such purchase order and expressly waived by the Customer.


This limited warranty does not cover or include any consumable/wearable products, such as filters or brushes, associated with such equipment.

Fountain assumes no liability for any unauthorized modifications carried out to the equipment not strictly recommended by the factory procedures or recommendations.

This limited warranty is not transferable, and does not cover any general equipment maintenance, demonstration, installation, routine servicing, calibration or customization of any equipment.

No person is authorized to alter or extend this limited warranty unless made in writing and signed by an authorized officer of Fountain.

DOC#: 303-002 REV: G UPDATED: 2/1/16



Fountain Industries LLC
4571 Valley Industrial Blvd. South Suite 300
Shakopee, MN 55379

Tel: 800-328-3594
507-373-2351

Email: CS@FTNLLC.COM
Website: WWW.FOUNTAININDUSTRIES.COM